

# 3030-RC Prep/Master®

Project sizes over 10,000 SF / 929 m<sup>2</sup>

It's a System  
**P/M**  
Not a Machine

**3030RC 230V -**  
**Item #418330230**

**3030RC 480V -**  
**Item #418330480**



Flooring Applications



**Concrete**



**Terrazzo**



**Marble**



**Granite**

## Specifications

Motor	30 HP - 3 phase   22kW
Power Source	220/230 VAC 3 Phase, 50-60 Hz 380/480 VAC 3 Phase, 50-60Hz
Power Cord	30 ft./9m (6-4)
Vacuum Hose Connection	3 in./76mm x 25 ft./8m
Weight	1,850 lbs.   839 kg
Tool RPM	250RPM (30Hz) to 750RPM (90Hz)
Number of Tools	12
Tools Attachment Style	EG Proprietary Attachment System
Dimensions	97"L x 30"W x 64"H 246 cm x 76 cm x 163 cm
Recommended Vacuum	Duo Vac (630CFM) with pre-separator or equivalent

## Production Rates

Mastic Removal	600 SF /56 m <sup>2</sup> per hr
Thin Set Removal	600 SF /56 m <sup>2</sup> per hr
Mil Coatings Removal	425 SF /39 m <sup>2</sup> per hr
Polished Concrete	1,200 SF /111.5 m <sup>2</sup> per hr

## Diamond Systems for STI-3030RC



**Substrate Technology, Inc.**  
1384 Bungalow Rd.  
Morris, Illinois 60450

+1.815.941.4800  
Fax +1.815.941.4600  
[www.substratetechnology.com](http://www.substratetechnology.com)

It's a System  
**P/M**  
Not a Machine